


Features

- Frequency: 18-28GHz
- Small Signal Gain: 13.5dB
- P-1dB: 30dBm
- Psat: 30.5dBm
- Power Supply: +6V/520mA
- Input/Output: 50Ω
- Die Size: 2.6 x 1.5 x 0.1 mm

Functional Block Diagram

Typical Applications


- Test Instrumentation
- Microwave Radio & VSAT
- Military & Space
- Telecom Infrastructure
- Fiber Optics

Electrical Specifications


TA = +25°C, Vd = +6V, Vg=-0.85V, Ids=520mA

Parameters	Min.	Typ.	Max.	Units
Frequency	18-28			GHz
Small Signal Gain		13.5		dB
Gain Flatness	±0.5			dB
P-1dB		30		dBm
Psat		30.5		dBm
Input Return Loss		18		dB
Output Return Loss		21		dB
Quiescent Current		520		mA
* Adjust VG (-2V-0V), Recommended gate voltage -0.85V.				


Gain vs. Frequency




Isolation vs. Frequency




Input Return Loss vs. Frequency




Output Return Loss vs. Frequency



P-1dB vs. Frequency




Psat vs. Frequency





Outline Drawing:
All Dimensions in μm




Pad Description

Pad	Function	Description
1	RF IN	Signal input terminal, connected to 50 Ω circuit; no blocking capacitor required.
2	RF OUT	Signal output terminal, connected to 50 Ω circuit; no blocking capacitor required.
3, 4	VD1-2	Amplifier drain bias; external 10pF, 1000pF, 4.7uF bypass capacitor required.
5	VG1-2	Amplifier gate bias; external 10pF, 1000pF, 4.7uF bypass capacitor required.
Die bottom	GND	Die bottom must be connected to RF/DC ground.



Assembly Drawing



Note:

- C1 10pF
- C2 1000pF
- C3 4.7uF

Notes:

1. Die thickness: 100um
2. Typical bond pad is 100*100 μm²
3. Bond pad metalization: Gold
4. Backside metalization: Gold
5. Backside of the die (GND)
6. No connection required for unlabeled bond pads

Maximum Ratings:

1. Maximum drain voltage: +8V
2. Maximum gate bias: -3V
3. Maximum input power: +25dBm
4. Operating temperature: -55°C to +85°C
5. Storage temperature: -65°C to +150°C