

Features

- Frequency: 4-20GHz
- Insertion Loss: 0.7dB Typical
- Coupling: 15dB Typical
- Input/Output: 50Ω
- Chip Size: 2.02 x 1.33 x 0.1mm

Typical Applications


- Test Instrumentation
- Microwave Radio & VSAT
- Military & Space
- Telecom Infrastructure
- Fiber Optics

Electrical Specifications


TA = +25°C

Parameters	Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency	4		12	12		20	GHz
Insertion Loss		0.6			0.7		dB
Nominal Coupling	12	14	16	17	17	18	dB
Frequency Sensitivity		±2.0			±1.5		dB
Isolation		28			28		dB
Input port Return Loss		-20			-18		dB
Output port Return Loss		-20			-18		dB
Coupling port Return Loss		-13			-10		dB


Functional Block Diagram




Insertion Loss vs. Frequency




Nominal Coupling vs. Frequency



Isolation vs. Frequency




Return Loss vs. Frequency





Outline Drawing: All Dimensions in μm



Notes:



1. Die thickness: 100 μm
2. Bond pad is 92*92 μm^2
3. Bond pad metalization: Gold
4. Backside metalization: Gold
5. Backside of the die (GND)

Absolute Maximum Ratings

RF Input Power (RFIN)	+40dBm
Operating Temperature	-55°C to +85 °C
Storage Temperature	-65°C to +150 °C




Assembly Drawing



No	Function	Description
1	RF IN	RF signal input or RF signal output
2	RF OUT	RF signal input or RF signal output
3	CI,CR	Coupled or Isolation ports, when used as isolation port, 50 ohm load must be connected.
4	LOAD	50 ohm Load
5	Die Bottom	Die bottom must be connected to RF ground.



Mounting & Bonding Techniques for MMICs



Direct Mounting

1. Typically, the die is mounted directly on the ground plane.
2. If the thickness difference between the substrate (thickness c) and the die (thickness d) exceeds 0.05 mm (i.e., $c - d > 0.05$ mm), it is recommended to first mount the die on a heat spreader, then attach the heat spreader to the ground plane.
3. Heat Spreader Material: Molybdenum-copper (MoCu) alloy is commonly used.
4. Heat Sink Thickness (b): Should be within the range of $(c - d - 0.05$ mm) to $(c - d + 0.05$ mm).
5. Spacing (a): The gap between the bare die and the 50Ω transmission line should typically be 0.05 mm to 0.1 mm. If the application frequency is higher than 40GHz, then this gap is recommended to be 0.05mm

Wire Bonding Interconnection

The connection between the die and the 50Ω transmission line is usually made using 25 μm diameter gold (Au) wires, bonded via wedge bonding or ball bonding processes.

Die Attachment Methods

1. Conductive Epoxy:

After adhesive application, cure according to the manufacturer's recommended temperature profile.

2. Au-Sn80/20 Eutectic Bonding:

Use preformed Au-Sn80/20 solder preforms.

Perform bonding in an inert atmosphere (N_2 or forming gas: 90% N_2 + 10% H_2).

Keep the time above 320°C to less than 20 seconds to prevent excessive intermetallic formation.

Miller MMIC Inc. All rights reserved

Miller MMIC, Inc. holds exclusive rights to the information presented in its Data Sheet and any accompanying materials. As a premier supplier of cutting-edge RF solutions, Miller MMIC has made this information easily accessible to its clients.

Although Miller MMIC believes the information provided in its Data Sheet to be trustworthy, the company does not offer any guarantees as to its accuracy. Therefore, Miller MMIC bears no responsibility for the use of this information. It is worth mentioning that the information within the Data Sheet may be altered without prior notification.

Customers are encouraged to obtain and verify the most recent and pertinent information before placing any orders for Miller MMIC products. The information in the Data Sheet does not confer, either explicitly or implicitly, any rights or licenses with regards to patents or other forms of intellectual property to any third party.

The information provided in the Data Sheet, or its utilization, does not bestow any patent rights, licenses, or other forms of intellectual property rights to any individual or entity, whether in regards to the information itself or anything described by such information. Furthermore, Miller MMIC products are not intended for use as critical components in applications where failure could result in severe injury or death, such as medical or life-saving equipment, or life-sustaining applications, or in any situation where failure could cause serious personal injury or death.